



VV-10 SLIM

VERTICAL REFRIGERATED DISPLAY CASES

- ✓ Pre-painted steel cabinet with polyurethane insulation, cyclopentane blown, HCFC-free.
- ✓ Swing-type Low-E double-pane tempered glass door. Self-closing with magnetic gasket.
- ✓ High-efficiency compressor with copper refrigeration circuit, silver-brazed.
- ✓ Removable condensing unit for easy maintenance.
- ✓ 100% copper refrigeration system.

Certifications

I 45001
S 14001
O 9001

VV-10 SLIM



Dimensions	Length (mm)	Depth (mm)	Height (mm)
External	500	575	1845
Internal	420	485	1375
Packaging	520	595	1875

Weight	Net Kg	Gross (Kg)
VV-10 SLIM	71	78

Interior Temperature	Ambient Condition
0°C / 5°C	32 °C / 65%RH

Capacity	Gross (L)	Net (L)
VV-10 SLIM	290	235

Capacity	Cans	Bottles
VV-10 SLIM	288u 350ml	100u 591ml

Shelf / Basket	Width (mm)	Depth (mm)
4 adjustable shelves	406	405

Commercial Reference - Compressor	Condenser Type
1/2 HP Inverter	Finned condenser
Refrigerant	R-290

Mimet Commitment

100% TESTED

Each unit is individually tested to guarantee quality and performance

100% TRACEABILITY

Every component and process is recorded to ensure full traceability throughout the product's lifecycle.

Container Capacity

Cont.20' 36 units

Cont.40' 76 units

Cont.40 HC

Electric Data

Voltage (V) 220

Frequency (Hz) 50

Current (A) 1

Power (W) 196

Energy Consumption (25°C / 60%RH) 2,39 KWh/día

Optional Accessories

Branding

Double LED Lighting

Sign Holder

Electronic Control

Helical condenser

Features

Hot-gas defrost water evaporation pan.

Efficient refrigeration system with forced-air circulation.

Temperature control with adjustable thermostat.

Condenser and evaporator with copper tubes and aluminum fins.

Hot-gas water evaporation pan.

Integrated interior LED lighting. Enables 20% electrical energy savings.

Adjustable plastic-coated steel rod shelves. Base with adjustable glides.

Certifications

I 45001
S 14001
O 9001

www.mimet.cl



mimet



@mimet.cl



contacto@mimet.cl



(56-2) 238 09 500

